



www.luofusv.com



罗浮阀门集团有限公司
LUOFU VALVE GROUP CO.,LTD.

地址：浙江永嘉瓯北东瓯工业园区 325105
Add : Dong'ou Ind. Zone, Oubei Town, Yongjia County, 325105, Zhejiang.
电话/Tel: +86 577 67988858 传真/Fax: +86 577 67988857
E-mail: safety@luofusv.com

www.luofusv.com

美标系列安全阀

罗浮阀门集团有限公司



罗浮阀门集团有限公司
LUOFU VALVE GROUP CO.,LTD.

地址：浙江永嘉瓯北东瓯工业园区 325105
Add : Dong'ou Ind. Zone, Oubei Town, Yongjia County, 325105, Zhejiang.
电话/Tel: +86 577 67988858
传真/Fax: +86 577 67988857
www.luofusv.com
E-mail: safety@luofusv.com



F

**LFNJ Series Pressure
Relief Valves With Jacket**

LFNJ 保温夹套式安全阀

Brief 企业简介 Introduction



罗浮阀门集团有限公司创建于1984年，位于中国泵阀之乡--美丽的瓯江北岸，浙江省永嘉县瓯北镇东瓯工业园区。原企业名称浙江罗浮锅炉附件厂。公司地理位置优越，陆、海、空交通便利。总注册资本10088万元人民币，总建筑面积6.5万m²。

公司主导产品有弹簧式直接载荷式安全阀、先导式安全阀、泄压阀、保温夹套式安全阀、高温高性能蒸汽安全阀、衬里安全阀和压力真空释放阀、紧急泄放阀等两类系列产品。安全阀系列产品结构分为美标、国标两大系列，压力等级：150Lb-2500Lb(PN1.6MPa~PN42MPa)，入口规格：1/2"~20" (DN15~DN500)。压力真空释放阀入口规格：2"~12" (DN50~DN300)，紧急泄放阀入口规格：16"~24" (DN400~DN600)。同时，公司还致力于满足用户要求，进行非标安全阀、呼吸阀产品的研发、设计、制造、验收。

公司始终以“立足质量、强化管理、持续改进、顾客至上”的企业方针，经过30多年的发展，构建了一套完整的、先进的和雄厚的安全阀的研发、制造、试验和检测体系。现有员工近200余人，其中技术人员共29人，中高级以上7人。公司拥有先进的机械加工中心、数控机床、普通机床、

铣床、钻床、氩弧焊机等设备200多台套。拥有金属材料理化试验室、机械性能力学试验室、安全阀全性能测试中心、低温冲击试验室、呼吸阀全性能试验装置，超声波测厚、无损探伤、光谱分析、金属热处理、弹簧拉压试验等专用设备。还新建了国内领先的安全阀低温试验台和具有超声波清洗的专业脱脂生产工段。

公司为了确保产品质量满足顾客要求，不断深化内部管理，全面提升全员质量意识。实行标准化、规范化、程序化管理，具有健全、完善和运行有效的质量管理体系。公司从1997年获得ISO9001质量管理体系认证开始，先后获取了“采用国际标准合格证”、“特种设备制造许可证”、美国工程师协会“ASME产品认证”、“欧盟CE认证”、“中国船级社(CCS)认证”、“API6D产品认证”、ISO14001环境管理体系和GB/T28001-2001职业健康安全管理体系认证。

公司从事阀门产品和储罐附件的设计与生产已有三十多年的历史，积累了丰富的设计和生产经验。在行业界已产生了积极的影响，树立了良好的口碑。现已成为中国石化集团物资装备公司资源市场成员单位、中国石油天然气集团公司一级网络供应商、能源一号网会员单位、中国海洋石油总公司网络供应商、中国蓝星(集团)总公司指定供应商、神华集团一级网络成员单位、中国化工集团合格供应商、惠生工程(中国)有限公司合格供应商等。胜利油田、中原油田勘探局、中国水

力电力物资公司、齐鲁石化供应公司等单位的物质资源市场供应网络成员，中国通用机械阀门行业协会、中国化工装备协会的成员单位。

公司产品已畅销全国，为石油、化工、煤化工、多晶硅、电力、医药等行业提供了质量可靠、价格合理的产品，受到广大用户的欢迎与好评。在国内各大城市已形成销售网络并树立了较高的知名度和信誉度，部分产品已远销欧美及中东等地区或国家。

我们坚持“过程精品，以人为本”的理念，以先进的技术、精细的管理、优质的质量、良好的售后服务，回报广大用户对我公司的厚爱。



Luofu Valve Group Co., Ltd was founded in 1984, situated in Dong'ou Ind. zone, Oubei Town, Yongjia county, Zhejiang which is a beautiful north bank of Oujiang River-The Chinese Capital of Pumps and Valves, and commands a favorable geographical location to offer nice transportation facilities by land, by sea or by air. Its original company name is Zhejiang Luofu Boiler Accessories Factory, and its total registered capital is CNY100.88 million with an overall construction area of 65 thousand sq.m.

The company engage in conventional pressure relief valve, balanced pressure relief valve, pilot operated pressure relief valve, pressure relief valve with jacket, high performance pressure relief valve for service steam, etc. and pressure/vacuum relief valve, emergency discharge valves, etc. The structure of Safety Valve series are divided into the ASME standard and the National standard. its pressure class is 150Lb-2500Lb(PN1.6MPa~PN42MPa), Inlet size: 1/2"~20" (DN15~DN500). Pressure/vacuum relief valve series'



We Enhance Competitive Force Through Innovative Technology

我们用创新科技提高竞争力

Inlet size: 2"~12" (DN50~DN300) while Emergency discharge valves is Inlet size: 16"~24" (DN400~DN600). In addition, the company is committed research, design, manufacture and inspection of non-standard Safety Valves and Pressure/vacuum Relief Valves in order to meet client satisfaction.

The company persists the enterprise policy "being based on quality, strengthening management, continuous improvement, and customer first", after more than 30 years of development to build a set of complete, advanced and strong research, manufacture, test and inspection system of safety valve series. It existing staff nearly 200 people, including 29 technicians and 7 senior technicians and owns CNC, CNC lathe, Lathe, Milling machine, Drilling machine, Tig welding machine etc.. and also owns metal material physical and chemical laboratory, mechanical properties of mechanics laboratory, relief valve performance testing center, low temperature impact test chamber, pressure/vacuum relief valve test device, ultrasonic thickness of metal heat treatment, nondestructive flaw detection, spectral analysis, spring tension and compression test. Also has built a safety valve of low temperature test rig and the ultrasonic cleaning equipment for skim.

The company constantly deepen the internal management and tries to enhance quality sense of all staff members in order to ensure the quality of products to meet client satisfaction. Therefore, the company conducts all round the standardization, normalization and routinization management based on a sound, impeccable and effective quality management system, it obtained successively the certifications of "International Standards Qualification", "Special Equipment Manufacturing License", the association of American engineers "ASME certification", "CE certification" "CCS certification", "API6D certification", "ISO4001 Environmental management system" and "GB/T28001-2001 occupational health and safety management system certification" since getting certified ISO9001 Quality system in 1997.

Over the past three decades the company has gained plenty of experience in design and production of valves and storage tank accessories, and has its positive influence and gets rewards in the valve industry. The company has become member of the resources market of Sinopec Supplies and Equipment Co., Ltd., Grade-A material supplier of CNPC (member of energyahead.com), CNOOC network provider, Grade-A member of Shenhua Group network, qualified supplier of China National Chemical Group, and qualified supplier of Wison Engineering (China) Co., Ltd. At the same time, our company has established good cooperative relations with Sinopec Luoyang Petrochemical Engineering Co., Ltd., PetroChina East China Investigation and Design Institute, China Tianchen Engineering Co., Ltd., China Chengda Engineering Co., Ltd., Hualu Engineering Technology Co., Ltd., East China Engineering Science and Technology Co., Ltd., Daqing Petrochemical Design Institute, Shengli Oil Institute, Fushun Petrochemical Design Institute and other relevant units, and signed strategic cooperation framework agreements with the refinery projects and ethylene projects of subordinate units of PetroChina, Sinopec, CNOOC.

The company's products have been sold well all over the country, to provide products with reliable quality, reasonable price for the petroleum, chemical industry, coal chemical industry, polysilicon, power, pharmaceutical and other industries, and was welcomed by the masses of clients. The sales network has been formed in major cities in the domestic and also set a higher visibility and credibility. The products have been exported to Europe, America and the Middle East etc.

We always adhere to the principle "Processing Excellence and Human Centered", and rebounding vast customers for their great kindness with advanced technology, scientific management, high quality and excellent after-sales service.

LFXY 泄压式

- 规格：1/4B1/4~1D1
- 压力级：Class150~2500
- 温度：-196℃~427℃

LFGS 高性能蒸汽式


- 规范：ASME 第 I 卷
- 规格：1 1/2"~6"
- 压力级：Class300~2500
- 温度：-29℃~538℃

LFNJ 保温夹套式

- 规格：1D2~8T10
- 压力级：Class150~300
- 温度：-196℃~538℃

LFCL 衬里式

- 规格：1"~8"
- 压力级：Class150~300
- 温度：-29℃~260℃



执行标准

- API RP520 炼油厂泄压设备尺寸确定、选型与安装
- API std521 泄压和降压系统之指南
- API std526 钢制法兰泄压阀
- API std527 泄压阀阀座的密封性
- ASME 美国机械工程师协会《锅炉与压力容器规范》第VIII卷《压力容器》
- ASME 美国机械工程师协会《锅炉与压力容器规范》第I卷《动力锅炉》
- ISO 4126-1 安全阀一般要求
- API607 阀门检查与测试
- API598 阀门的检验和测试
- ASME PTC25 泄压装置性能试验规范
- TSG ZF001-2006 安全阀安全技术监察规程

Execution Standard

- Sizing, Selection, and Installation of Pressure-Relieving Devices in Refineries
- Pressure-relieving and Depressuring systems
- Flanged Steel Pressure Relief Valves
- Seat Tightness of Pressure Relief Valves
- ASME Boiler and Pressure Vessel Code, Section I Division 1, Rules for Construction of Pressure Vessels
- ASME Boiler and Pressure Vessel Code, Section VIII Division 1, Rules for Construction of Power Boilers
- Safety Devices for Protection Against Excessive Pressure
- Valve Inspection and Test
- Valve Inspection and Test
- Pressure Relief Devices Performance Test Codes
- Safety Technical Supervision Regulations for Safety Valves

安全阀定径的公式和密封验收的标准

PRESSURE RELIEF VALVES SIZING FORMULA AND SEAL OF ACCEPTANCE CRITERIA

定径——摘自API Std 520 Sizing-Extract from API Std 520

1 气体和蒸汽的定径程序

首先要确定其流动状态，具体程序为：

- (1) 计算安全阀背压与额定排放压力绝压数值的比 P_b/P_{dr} ；
- (2) 按下式计算临界流动压力 P_{cf}/P_{dr} ：

$$\frac{P_{cf}}{P_{dr}} = \left[\frac{2}{k+1} \right]^{k/(k-1)}$$

- (3) 若 $\frac{P_b}{P_{dr}} > \frac{P_{cf}}{P_{dr}}$ ，则可确定流动为亚临界流动；
- 若 $\frac{P_b}{P_{dr}} \leq \frac{P_{cf}}{P_{dr}}$ ，则可确定流动为临界流动。

式中：

P_b	=	背压，即附加背压和排放背压的和，再加上大气压，MPa(a)
P_{dr}	=	额定排放压力，该压力等于整定压力加上允许超过压力，再加上大气压， $P_{dr} = P_s \times (1 + \Delta P_0) + P_{atm}$ ，MPa(a)
P_s	=	整定压力，MPa(g)
P_{atm}	=	大气压力，取0.103MPa
P_{cf}	=	出口临界流动压力
k	=	气体的比热比



“诚招天下客，誉从质中来”。长期以来，公司十分注重与客户的友好合作，保证品质与服务，珍视荣誉，从而赢得了客户的信赖与支持。与朋友广泛合作，共享繁荣，也成为我们最真诚的追求。

Soliciting clients in earnest, Win reputation by quality. In order to win the customer's trust and support, our company always attache great importance to friendly cooperate with customers, to ensure quality and service, and to value honor. To widely cooperate with friends and to share prosperity, has become our most sincere pursuit.




www.luofusv.com

LUOFU VALVE GROUP CO.,LTD.
罗浮阀门集团有限公司



Qualification Certificate 资质证书



Production Equipment 生产装备

With Elaborate Production Technology, Strict Quality Guarantee System, LUOFU Provides Solid Guarantee for Each Component.

精湛的生产工艺严格的质保体系，罗浮为任一零件提供严格的保障



In excellent equipment and strict quality management, based on the condensation of the technology and the essence of wisdom, has been engaged in the development of industrial fluid control and manufacturing. In the era of environment, and strive to even or half-step ahead of the technology, while the "entrepreneurial spirit, innovation" as the goal to meet customer needs to carry out fluid control research and development activities. We hope that through our comprehensive design, manufacturing and after-sales

service, to ensure effective use of each product in full play during the design of performance indicators. We have advanced manufacturing methods, complete testing facilities. Full implementation of computer-aided manufacturing, to ensure product quality and efficiency. Application of digital technology direct dialogue programming, the implementation of drilling, cutting, milling, grinding process on the key components such as mechanical processing, ensure extreme accuracy.

在设备优良和严格质量管理的基础上，凝结睿智的技术和精髓，一直投身于工业流体控制的研发和制造中。在时代环境下，力争哪怕是领先一步或半步的技术优势，同时以“创业精神、技术革新”为目标，开展能满足客户需求的流体控制研发活动。我们希望通过我们完善的设计、制造和售后服务，确保每一台产品在有效使用期内充份发挥各项设计性能指标。我们拥有先进的制造手段，完备的检测设施。全面推行计算机辅助制造，确保产品质量及工效。应用数字技术进行直接对话式编程，实施钻、削、铣、磨等工艺对关键部件进行机械加工，确保产品极限精度。

气体和蒸汽的定径公式

A = (13.16 * W) / (C * Kdr * Pdr * Kb * Kc) * sqrt(TZ / M) (1)

式中：

A	=	所需的有效排放面积，mm ²
W	=	所需泄放量，kg/h
C	=	根据气体或蒸气在入口排放条件下的比热比（k=C _p /C _v ） 确定的系数，由下面公式确定 C = 520 * sqrt(2 / (k * (k+1)^(k-1) / (k-1)))
K _{dr}	=	额定排量系数
P _{dr}	=	额定排放压力，该压力等于整定压力加上允许超过压力， 再加上大气压，P _{dr} = P _s × (1 + ΔP ₀) + P _{atm} ，MPa(a)
K _b	=	排量的背压修正系数 对于常规式和先导式泄压阀，当为临界流动时，K _b 等于1.0；当为亚临界流 动时，K _b = sqrt(2 * [(r)^(2/k) - r^(k+1/k)] / ((k-1) * (2 / (k+1))^(k+1 / (k-1))))，其中r为背压对上游排放压力的比值，P _b / P _{dr} 对于平衡波纹管式泄压阀，超压21%时，且P _b /P _s 小于等于50%时，K _b 等 于1.0；超压10%和16%时，由图1确定
K _c	=	当泄压阀上游装有爆破片时的联合修正系数
	=	当不安装爆破片时，取1.0
	=	当爆破片与泄压阀联合安装，取0.9
T	=	入口气体或蒸气的排放温度，K(°C+273)
Z	=	压缩因子
M	=	气体和蒸气在入口排放状态下的摩尔质量，kg/kmole




图1- 平衡波纹管式泄压阀（蒸汽和气体）的背压修正系数，K_b

2 蒸汽的定径程序

A = (W) / (5.25 * Pdr * Kdr * Kb * Kc * KN * KSH) (2)

式中：

A	=	所需的有效排放面积，mm ²
W	=	所需泄放量，kg/hr
P _{dr}	=	额定排放压力，该压力等于整定压力加上允许超过压力， 再加上大气压，P _{dr} = P _s × (1 + ΔP ₀) + P _{atm} ，MPa(a)
K _{dr}	=	额定排量系数
K _b	=	排量的背压修正系数 对于常规式和先导式泄压阀，当为临界流动时，K _b 等于1.0； 当为亚临界流动时，K _b = sqrt(2 * [(r)^(2/k) - r^(k+1/k)] / ((k-1) * (2 / (k+1))^(k+1 / (k-1))))，其中r为背压对上游排放压力 的比值，P _b / P _{dr} 。对于平衡波纹管式泄压阀，超压21%时，且P _b /P _s 小于等于 50%时，K _b 等于1.0；超压10%和16%时，由图1确定
K _c	=	当泄压阀上游装有爆破片时的联合修正系数
	=	当不安装爆破片时，取1.0
	=	当爆破片与泄压阀联合安装，取0.9
K _N	=	Napier公式的修正系数
	=	当 P _{dr} ≤ 10.339MPa(a) 时，取1；
	=	P ₁ > 10.339MPa(a)且≤22,057MPa(a)时，为 (27.64 * P _{dr} - 1000) / (33.24 * P _{dr} - 1061)
K _{SH}	=	过热蒸汽修正系数，见下表：

Inspection And Test 检测试验

**Rigorous, Efficient
Pragmatic, Innovation**
高效 务实 严谨 创新

本着“质量是企业的生命，信誉是企业的根本”这一理念，全面强化质量管理，建立质量保证体系，对产品实行全过程的质量控制。罗浮拥有自己的一整套质量控制程序，从原材料、外协件进厂到零部件加工、成品最终出厂检验，都应用计算机网络管理系统，建立产品质量档案，实现产品可追溯性管理。我们坚持“经顾客为中心，实现顾客零抱怨；以体系为基础，追求产品零缺陷”的质量方针，推行用户满意工程，满足顾客的需求和期望。

Based on the conception of quality is the life of the enterprise and reputation is the base of the enterprise, our company establishes quality guarantee system to carry out whole-course quality control for the products. Luofu has a whole set of quality control procedures of its own. From the incoming of raw materials and outsourcing parts, the machining of parts to the outgoing quality control of finished production, the computer network management system is applied and product quality files are established so as to realize product traceability management. By insisting on the quality policy of customer centered to realize zero complaint of customers, based on system to seek for zero defect of products, we are pushing forward customer satisfactory project so as to satisfy customer demands and expects.



1、金相分析 Metallographic Analysis



2、硬度仪 Hardness Tester



3、碳硫分析仪 Carbon and Sulfur Analyzer



4、机械性能试验 Mechanical Test



5、UT检测仪 UT Detector



6、低温冲击 Low Temperature Impact Test

Quality is Represented by the Incomparable Reliability and Performance of Products.
品质表现在产品无与伦比的可靠性



7、MT检测仪 MT Detector



8、光谱仪 Mobile Spectrometer



9、防火试验 Fire Test



10、低温试验 Low Temperature Test



11、化学分析 Chemical Analysis





特点

- 用作聚酯、乙烯及尿素化肥等装置中介质需要保温的压力安全附件。
- 对进、出口法兰在内的阀体均进行保温、因而保温效果好；特殊需要时可增加蒸汽冲洗功能。
- 平衡波纹管式结构，变动背压不影响安全阀的整定压力，且波纹管对弹簧等阀盖内的里零件起到防护介质侵蚀作用。
- 内件（阀瓣、阀座）标准材料均为奥氏体不锈钢且堆焊钴基硬质合金。
- 特殊需要时内件可提供尿素级316L、双相不锈钢0Cr25Ni6Mo3CuN（255合金）、00Cr25Ni6Mo2N(SUS329J1)等材质，波纹管可提供钛（Ti）材质。

Features

- It's serviced in the circumstance where the heat preservation of fluid is needed ,such as the equipment of polyester ,ethylene, urea, etc.
- Body including inlet and outlet flanges is heat preserved,so the effect is very well. The function of vapor flushing can be added, if needed.
- Balanced bellows construction protects set pressure from being affected by variable back pressure, and the parts in bonnet ,such as spring, from being corroded.
- The standard materials for the inside parts(Valve clack, valve seat) are all austenitic stainless steel and bead welding cobalt-base hard alloy.
- To meet special service, the material of trim can be 316LN, 0Cr25Ni6Mo3CuN(255 alloy)、and 00Cr25Ni6Mo2N(SUS329J1), the material of bellows can be Ti.

LFNJ保温夹套式安全阀结构 LFNJ Series Pressure Relief Valves With Jacket





表7 安全阀材料标准配置表 Table 7 Materials

序号 Ref. No	零件名称 Part Name	材料代号Sign of Materials								
		C	CS	CS1	CSL	S	S1	S2	SM	SL
1	阀体Body	WCB	WCB	WCB	WCB	CF8	CF8	CF3	CF8M	CF3M
2	阀座Nozzle	304	316	304L	316L	316	304	304L	361L	361L
5	阀瓣Disc	304	316	304L	316L	316	304	304L	316L	316L
4	调节圈Nozzle Ring	CF8M	CF8M	CF8M	CF8M	CF8M	CF8M	CF3M	CF8M	CF3M
3	定位螺钉Set Screw	304	304	304L	304	304	304	304L	316	316L
6	反冲盘Disc Holder	420	420	420	420	420	420	420	630	630
7	导套Guide	304	304	304L	304	304	304	304L	316(304)	316L(304)
8	弹簧座Spring washer	碳钢C.St.	碳钢C.St.	碳钢C.St.	碳钢C.St.	420	420	420	420	420
9	弹簧Spring	合金钢 Alloy St.	合金钢 Alloy St.	合金钢 Alloy St.	合金钢 Alloy St.	不锈钢/合金钢 St.St./Alloy	不锈钢/合金钢 St.St./Alloy	不锈钢/合金钢 St.St./Alloy	不锈钢/合金钢 St.St./Alloy	不锈钢/合金钢 St.St./Alloy
10	阀杆Spindle	420	420	420	420	420	420	420	630(420)	630(420)
11	阀盖Bonnet	WCB	WCB	WCB	WCB	CF8	CF8	CF8	CF8M(CF8)	CF8M (CF8)
12	调整螺钉Adjusting Bolt	420	420	420	420	420	420	420	420	420
13	阀帽Cap	WCB	WCB	WCB	WCB	CF8	CF8	CF3M	CF8	CF8
14	锁紧螺母Adj Bolt Nut	碳钢C.St.	碳钢C.St.	碳钢C.St.	碳钢C.St.	420	420	420	420	420
15	波纹管Bellows	316L	316L	316L	316L	316L	316L	316L	无(316L)	无 (316L)

LFNJ 型号编制说明 Code system

代号 Code	1	-	2	3	4	5	6	7	8
实例 Example	LFNJ	-	F	1	1	01	01	C	B



LFNJ口径、压力-温度范围 Size、Pressure-Temperature Limits

流道面积 Orifice Area (mm ²)	进出口法兰压力等级代号 Flange Code	阀门规格 Size	法兰等级 Flange Class		最高整定压力 (MPa) Maximum Set Pressure						材料Materials	
					进口温度 (°C) Inlet Temperature						阀体/阀盖 Body/ Bonnet	进口温度范围 (°C) Inlet Temp. Range
			进口 Inlet	出口 Outlet	-268~ -60	-59 ~ -29	-29 ~ 38	38 ~ 232	233 ~ 427	427 ~ 538		
D API:71.0 实际 ACTUAL: 86.6	0101	1D2 (2.5)	150	150			1.96	1.27	0.55		碳钢 Carbon Steel.	-29~425
	0301	1D2 (2.5)	300	150			1.96	1.96	1.96			
	03a01	1D2 (2.5)	300	150			5.1	4.24	2.82			
	0101	1D2 (2.5)	150	150	1.89	1.89	1.89	1.24	0.55	0.13	奥氏体不锈钢 Austenitic Stainless Steel	-196-538
	0301	1D2 (2.5)	300	150	1.89	1.89	1.89	1.89	1.89	1.89		
	03a01	1D2 (2.5)	300	150	4.96	4.96	4.96	3.41	2.89	2.41		
E API:126 实际 ACTUAL: 153.9	0101	1E2 (2.5)	150	150			1.96	1.27	0.55		碳钢 Carbon Steel.	-29~425
	0301	1E2 (2.5)	300	150			1.96	1.96	1.96			
	03a01	1E2 (2.5)	300	150			5.1	4.24	2.82			
	0101	1E2 (2.5)	150	150	1.89	1.89	1.89	1.24	0.55	0.13	奥氏体不锈钢 Austenitic Stainless Steel	-196-538
	0301	1E2 (2.5)	300	150	1.89	1.89	1.89	1.89	1.89	1.89		
	03a01	1E2 (2.5)	300	150	4.96	4.96	4.96	3.41	2.89	2.41		
F API:198 实际 ACTUAL: 227.0	0101	1.5F2 (2.5)	150	150			1.96	1.27	0.55		碳钢 Carbon Steel.	-29~425
	0301	1.5F2 (2.5)	300	150			1.96	1.96	1.96			
	03a01	1.5F2 (2.5)	300	150			5.1	4.24	2.82			
	0101	1.5F2 (2.5)	150	150	1.89	1.89	1.89	1.24	0.55	0.13	奥氏体不锈钢 Austenitic Stainless Steel	-196-538
	0301	1.5F2 (2.5)	300	150	1.89	1.89	1.89	1.89	1.89	1.89		
	03a01	1.5F2 (2.5)	300	150	4.96	4.96	4.96	3.41	2.89	2.41		

LFNJ SERIES PRESSURE RELIEF VALVES WITH JACKET

LFNJ SERIES PRESSURE RELIEF VALVES WITH JACKET

LFNJ口径、压力-温度范围 Size、Pressure-Temperature Limits

流道面积 Orifice Area (mm ²)	进出口法兰压力等级代号 Flange Code	阀门规格 Size	法兰磅级 Flange Class		最高整定压力 (MPa) Maximum Set Pressure						材料Materials	进口温度范围 (°C) Inlet Temp. Range
					进口温度 (°C) Inlet Temperature						阀体/阀盖 Body/ Bonnet	
			进口 Inlet	出口 Outlet	-268~	-59 ~	-29 ~	38 ~	233 ~	427 ~		
					-60	-29	38	232	427	538		
G API:324 实际 ACTUAL: 363.1	0101	1.5G3 (4)	150	150			1.96	1.27	0.55		碳钢 Carbon Steel.	-29~425
	0301	1.5G3 (4)	300	150			1.96	1.96	1.96			
	03a01	1.5G3 (4)	300	150			5.1	4.24	2.82			
	0101	1.5G3 (4)	150	150	1.89	1.89	1.89	1.24	0.55	0.13	奥氏体不锈钢 Austenitic Stainless Steel	-196-538
	0301	1.5G3 (4)	300	150	1.89	1.89	1.89	1.89	1.89	1.89		
	03a01	1.5G3 (4)	300	150	4.96	4.96	4.96	3.41	2.89	2.41		
H API:506 实际 ACTUAL: 572.6	0101	1.5H3 (4)	150	150			1.96	1.27	0.55		碳钢 Carbon Steel.	-29~425
	0301	1.5H3 (4)	300	150			1.96	1.96	1.96			
	03a01	2H3 (4)	300	150			5.1	4.24	2.82			
	0101	1.5H3 (4)	150	150	1.89	1.89	1.89	1.24	0.55	0.13	奥氏体不锈钢 Austenitic Stainless Steel	-196-538
	0301	1.5H3 (4)	300	150	1.89	1.89	1.89	1.89	1.89	1.89		
	03a01	2H3 (4)	300	150	4.96	4.96	4.96	3.41	2.89	2.41		
J API:830 实际 ACTUAL: 934.8	0101	2J3 (4)	150	150			1.96	1.27	0.55		碳钢 Carbon Steel.	-29~425
	0301	2J3 (4)	300	150			1.96	1.96	1.96			
	03a01	3J4 (6)	300	150			5.1	4.24	2.82			
	0101	2J3 (4)	150	150	1.89	1.89	1.89	1.24	0.55	0.13	奥氏体不锈钢 Austenitic Stainless Steel	-196-538
	0301	2J3 (4)	300	150	1.89	1.89	1.89	1.89	1.89	1.89		
	03a01	3J4 (6)	300	150	3.44	4.96	4.96	3.41	2.89	2.41		

LFNJ口径、压力-温度范围 Size、Pressure-Temperature Limits

流道面积 Orifice Area (mm ²)	进出口法 兰压力等 级代号 Flange Code	阀门规格 Size	法兰磅级 Flange Class		最高整定压力 (MPa) Maximum Set Pressure						材料Materials	进口温度 范围 (°C) Inlet Temp. Range
					进口温度 (°C) Inlet Temperature						阀体/阀盖 Body/ Bonnet	
			进口 Inlet	出口 Outlet	-268~	-59 ~	-29 ~	38 ~	233 ~	427 ~		
					-60	-29	38	232	427	538		
K API:1186 实际 ACTUAL: 1352.7	0101	3K4 (6)	150	150			1.96	1.27	0.55		碳钢 Carbon Steel.	-29~425
	0301	3K4 (6)	300	150			1.96	1.96	1.96			
	03a01	3K4 (6)	300	150			5.1	4.24	2.82			
	0101	3K4 (6)	150	150	1.89	1.89	1.89	1.24	0.55	0.13	奥氏体不锈钢 Austenitic Stainless Steel	-196-538
	0301	3K4 (6)	300	150	1.89	1.89	1.89	1.89	1.89	1.89		
	03a01	3K4 (6)	300	150	3.61	4.96	4.96	3.41	2.89	2.41		
L API:1841 实际 ACTUAL: 2083.1	0101	3L4 (6)	150	150			1.96	1.27	0.55		碳钢 Carbon Steel.	-29~425
	0301	3L4 (6)	300	150			1.96	1.96	1.96			
	03a01	4L6 (8)	300	150			5.1	4.24	2.82			
	0101	3L4 (6)	150	150	1.89	1.89	1.89	1.24	0.55	0.13	奥氏体不锈钢 Austenitic Stainless Steel	-196-538
	0301	3L4 (6)	300	150	1.89	1.89	1.89	1.89	1.89	1.89		
	03a01	4L6 (8)	300	150	3.68	4.96	4.96	3.41	2.89	2.41		
M API:2323 实际 ACTUAL: 2642.1	0101	4M6 (8)	150	150			1.96	1.27	0.55		碳钢 Carbon Steel.	-29~425
	0301	4M6 (8)	300	150			1.96	1.96	1.96			
	03a01	4M6 (8)	300	150			5.1	4.24	2.82			
	0101	4M6 (8)	150	150	1.89	1.89	1.89	1.24	0.55	0.13	奥氏体不锈钢 Austenitic Stainless Steel	-196-538
	0301	4M6 (8)	300	150	1.89	1.89	1.89	1.89	1.89	1.89		
	03a01	4M6 (8)	300	150	3.61	4.96	4.96	3.41	2.89	2.41		
N API:2800 实际 ACTUAL: 3166.9	0101	4N6 (8)	150	150			1.96	1.27	0.55		碳钢 Carbon Steel.	-29~425
	0301	4N6 (8)	300	150			1.96	1.96	1.96			
	03a01	4N6 (8)	300	150			5.1	4.24	2.82			
	0101	4N6 (8)	150	150	1.89	1.89	1.89	1.24	0.55	0.13	奥氏体不锈钢 Austenitic Stainless Steel	-196-538
	0301	4N6 (8)	300	150	1.89	1.89	1.89	1.89	1.89	1.89		
	03a01	4N6 (8)	300	150	3.1	4.96	4.96	3.41	2.89	2.41		

LFNJ SERIES PRESSURE RELIEF VALVES WITH JACKET

LFNJ SERIES PRESSURE RELIEF VALVES WITH JACKET

LFNJ口径、压力-温度范围 Size、Pressure-Temperature Limits

流道面积 Orifice Area (mm ²)	进出口法 兰压力等 级代号 Flange Code	阀门规格 Size	法兰磅级 Flange Class		最高整定压力 (MPa) Maximum Set Pressure						材料Materials	进口温度 范围 (℃) Inlet Temp. Range
					进口温度 (℃) Inlet Temperature						阀体/阀盖 Body/ Bonnet	
			进口 Inlet	出口 Outlet	-268~	-59 ~	-29 ~	38 ~	233 ~	427 ~		
					-60	-29	38	232	427	538		
P API:4116 实际 ACTUAL: 4656.6	0101	4P6 (8)	150	150			1.96	1.27	0.55		碳钢 Carbon Steel.	-29~425
	0301	4P6 (8)	300	150			1.96	1.96	1.96			
	03a01	4P6 (8)	300	150			3.61	3.61	2.82			
	0101	4P6 (8)	150	150	1.2	1.89	1.89	1.24	0.55	0.13	奥氏体不锈钢 Austenitic Stainless Steel	-196-538
	0301	4P6 (8)	300	150	1.2	1.89	1.89	1.89	1.89	1.89		
	03a01	4P6 (8)	300	150	2.06	3.61	3.61	3.41	2.89	2.41		
Q API:7129 实际 ACTUAL: 8171.3	0101	6Q8 (10)	150	150			1.13	1.13	0.55		碳钢 Carbon Steel.	-29~425
	0301	6Q8 (10)	300	150			1.13	1.13	1.13			
	03a01	6Q8 (10)	300	150			2.06	2.06	2.06			
	0101	6Q8 (10)	150	150	1.13	1.13	1.13	1.13	0.55	0.13	奥氏体不锈钢 Austenitic Stainless Steel	-196-538
	0301	6Q8 (10)	300	150	1.13	1.13	1.13	1.13	1.13	1.13		
	03a01	6Q8 (10)	300	150	1.72	2.06	2.06	2.06	2.06	2.06		
R API:10323 实际 ACTUAL: 11689.9	0101	6R8 (10)	150	150			0.68	0.68	0.55		碳钢 Carbon Steel.	-29~425
	0301	6R8 (10)	300	150			0.68	0.68	0.68			
	03a01	6R10 (12)	300	150			1.58	1.58	1.58			
	0101	6R8 (10)	150	150	0.37	0.68	0.68	0.68	0.55	0.13	奥氏体不锈钢 Austenitic Stainless Steel	-196-538
	0301	6R8 (10)	300	150	0.37	0.68	0.68	0.68	0.68	0.68		
	03a01	6R10 (12)	300	150	1.03	1.58	1.58	1.58	1.58	1.58		
T API:16774 实际 ACTUAL: 19113.4	0101	8T10 (12)	150	150			0.44	0.44	0.44		碳钢 Carbon Steel.	-29~425
	0301	8T10 (12)	300	150			0.44	0.44	0.44			
	03a01	8T10 (12)	300	150			0.82	0.82	0.82			
	0101	8T10 (12)	150	150	0.34	0.44	0.44	0.44	0.44	0.13	奥氏体不锈钢 Austenitic Stainless Steel	-196-538
	0301	8T10 (12)	300	150	0.34	0.44	0.44	0.44	0.44	0.44		
	03a01	8T10 (12)	300	150	0.44	0.82	0.82	0.82	0.82	0.82		

LFNJ 尺寸 Dimensions mm

流道 Orifice (mm)	进出口 法兰压力 代号 Flange Code	规格 Size	面心距 Center to Face		法兰尺寸 Dimensions						近似高度 Approximate Height H		近似重量 Approximate Weight , Cap Type B (Kg)
			出口 Outlet	进口 Inlet	进口 Inlet	D	K	d	f	n-M	阀帽型式 Cap Type		
L	L1	出口 Outlet	D1	K1	D1	C1	n1- φ 1	B	E				
D 10.5	0101	1D2(2.5)	134	125	进口Inlet	160	79.5	51	18	4-M14	425	485	19
					出口Outlet	178	139.5	105	22.4	4-φ 19			
	0301	1D2(2.5)	134	125	进口Inlet	160	89	51	18	4-M16	425	485	20
					出口Outlet	178	139.5	105	22.4	4-φ 19			
	03a01	1D2(2.5)	134	125	进口Inlet	160	89	51	18	4-M16	425	485	20
					出口Outlet	178	139.5	105	22.4	4-φ 19			
E 14.0	0101	1E2(2.5)	134	125	进口Inlet	160	79.5	51	18	4-M14	425	485	19
					出口Outlet	178	139.5	105	22.4	4-φ 19			
	0301	1E2(2.5)	134	125	进口Inlet	160	89	51	18	4-M16	425	485	20
					出口Outlet	178	139.5	105	22.4	4-φ 19			
	03a01	1E2(2.5)	134	125	进口Inlet	160	89	51	18	4-M16	425	485	20
					出口Outlet	178	139.5	105	22.4	4-φ 19			
F 17.0	0101	1.5F2(2.5)	140	139	进口Inlet	170	98.5	73	20	4-M14	439	499	22
					出口Outlet	178	139.5	105	22.4	4-φ 19			
	0301	1.5F2(2.5)	140	139	进口Inlet	170	114.5	73	20	4-M20	439	499	25
					出口Outlet	178	139.5	105	22.4	4-φ 19			
	03a01	1.5F2(2.5)	140	139	进口Inlet	170	114.5	73	20	4-M20	439	499	32
					出口Outlet	178	139.5	105	22.4	4-φ 19			
G 21.5	0101	1.5G3(4)	149	149	进口Inlet	190	98.5	73	20	4-M14	455	504	26
					出口Outlet	229	190.5	157	23.9	8-φ 19			
	0301	1.5G3(4)	149	149	进口Inlet	190	114.5	73	20	4-M20	455	504	29
					出口Outlet	229	190.5	157	23.9	8-φ 19			
	03a01	1.5G3(4)	149	149	进口Inlet	190	114.5	73	20	4-M20	455	504	37
					出口Outlet	229	190.5	157	23.9	8-φ 19			
H 27.0	0101	1.5H3(4)	155	150	进口Inlet	190	98.5	73	20	4-M14	456	505	29
					出口Outlet	229	190.5	157	23.9	8-φ 19			
	0301	1.5H3(4)	155	150	进口Inlet	190	114.5	73	20	4-M20	456	505	31
					出口Outlet	229	190.5	157	23.9	8-φ 19			
	03a01	1.5H3(4)	155	150	进口Inlet	190	114.5	73	20	4-M20	456	505	34
					出口Outlet	229	190.5	157	23.9	8-φ 19			
J 34.5	0101	2J3(4)	155	150	进口Inlet	200	120.5	92	20	4-M16	456	505	36
					出口Outlet	229	190.5	157	23.9	8-φ 19			
	0301	2J3(4)	155	150	进口Inlet	200	127	92	20	8-M16	456	505	38
					出口Outlet	229	190.5	157	23.9	8-φ 19			
	03a01	3J4(6)	185	170	进口Inlet	200	168	127	22	8-M20	565	610	65
					出口Outlet	229	241.5	216	25.4	8-φ 22			
K 41.5	0101	3K4(6)	185	170	进口Inlet	250	152.5	127	22	4-M16	565	610	65
					出口Outlet	279	241.5	216	25.4	8-φ 22			
	0301	3K4(6)	185	170	进口Inlet	250	168	127	22	8-M20	565	610	67
					出口Outlet	279	241.5	216	25.4	8-φ 22			
	03a01	3K4(6)	185	170	进口Inlet	250	168	127	22	8-M20	565	610	67
					出口Outlet	279	241.5	216	25.4	8-φ 22			


LFNJ 保温夹套式安全阀

LF-6

LFNJ SERIES PRESSURE RELIEF VALVES WITH JACKET

LFNJ 尺寸 Dimensions mm

流道 Orifice (mm)	进出口 法兰压力 代号 Flange Code	规格 Size	面心距 Center to Face		法兰尺寸 Dimensions						近似高度 Approximate Height H		近似重量 Approximate Weight , Cap Type B (Kg)
			出口 Outlet	进口 Inlet	进口 Inlet	D	K	d	f	n-M	阀帽型式 Cap Type		
											L	L1	
L	0101	3L4(6)	185	170	进口Inlet	250	152.5	127	22	4-M16	565	610	68
					出口Outlet	279	241.5	216	25.4	8-φ22			
	0301	3L4(6)	185	170	进口Inlet	250	168	127	22	8-M20	565	610	70
					出口Outlet	279	241.5	216	25.4	8-φ22			
51.5	03a01	4L6(8)	225	200	进口Inlet	250	200	157	22	8-M20	745	785	112
					出口Outlet	279	298.5	270	25.4	8-φ22			
	0101	4M6(8)	225	200	进口Inlet	320	190.5	157	22	8-M16	745	785	120
					出口Outlet	343	298.5	270	28.4	8-φ22			
M	0301	4M6(8)	225	200	进口Inlet	320	200	157	22	8-M20	745	785	123
					出口Outlet	343	298.5	270	28.4	8-φ22			
	03a01	4M6(8)	225	200	进口Inlet	320	200	157	22	8-M20	745	785	123
					出口Outlet	343	298.5	270	28.4	8-φ22			
58.0	0101	4N6(8)	225	200	进口Inlet	320	190.5	157	22	8-M16	745	785	123
					出口Outlet	343	298.5	270	28.4	8-φ22			
	0301	4N6(8)	225	200	进口Inlet	320	200	157	22	8-M20	745	785	127
					出口Outlet	343	298.5	270	28.4	8-φ22			
N	03a01	4N6(8)	225	200	进口Inlet	320	200	157	22	8-M20	745	785	127
					出口Outlet	343	298.5	270	28.4	8-φ22			
	0101	4P6(8)	225	200	进口Inlet	320	190.5	157	22	8-M16	745	785	124
					出口Outlet	343	298.5	270	28.4	8-φ22			
P	0301	4P6(8)	225	200	进口Inlet	320	200	157	22	8-M20	745	785	131
					出口Outlet	343	298.5	270	28.4	8-φ22			
	03a01	4P6(8)	225	200	进口Inlet	320	200	157	22	8-M20	745	785	131
					出口Outlet	343	298.5	270	28.4	8-φ22			
77.0	0101	6Q8(10)	256	239.5	进口Inlet	370	241.5	216	22	8-M20	859.5	889.5	159
					出口Outlet	406	362	324	30.2	12-φ26			
	0301	6Q8(10)	256	239.5	进口Inlet	370	270	216	22	12-M20	859.5	889.5	218
					出口Outlet	406	362	324	30.2	12φ26			
102.0	03a01	6Q8(10)	256	239.5	进口Inlet	370	270	216	22	12-M20	859.5	889.5	226
					出口Outlet	406	362	324	30.2	12-φ26			
	0101	6R8(10)	276	239.5	进口Inlet	410	241.5	216	22	8-M20	859.5	889.5	168
					出口Outlet	406	362	324	30.2	12-φ26			
R	0301	6R8(10)	276	239.5	进口Inlet	410	270	216	22	12-M20	859.5	889.5	242
					出口Outlet	406	362	324	30.2	12-φ26			
	03a01	6R10(12)	282	269	进口Inlet	420	270	216	22	12-M20	889	919	292
					出口Outlet	483	432	381	32	12-φ26			
122.0	0101	8T10(12)	310	280	进口Inlet	480	298.5	270	22	8-M20	1167	1250	414
					出口Outlet	483	432	381	32	12-φ26			
	0301	8T10(12)	310	280	进口Inlet	480	330	270	22	12-M24	1167	1250	424
					出口Outlet	483	432	381	32	12-φ26			
156.0	03a01	8T10(12)	310	280	进口Inlet	480	330	270	22	12-M24	1167	1250	424
					出口Outlet	483	432	381	32	12-φ26			



罗浮阀门集团有限公司
LUOFU VALVE GROUP CO.,LTD.

地址：浙江永嘉瓯北东瓯工业园区 325105
Add : Dong'ou Ind. Zone, Oubei Town, Yongjia
County, 325105, Zhejiang.
电话/Tel: +86 577 67988858
传真/Fax: +86 577 67988857
www.luofusv.com
E-mail: safety@luofusv.com

LFCL Lining Type
Pressure Relief Valves
LFCL 衬里式安全阀